

FEATURES

Compaq ProLiant 1600

Compaq ProLiant 1600 6/266

Compaq ProLiant 1600 6/300

System Unit

Microprocessor	266-MHz Intel Pentium® II processor	300-MHz Intel Pentium II processor
Upgradability	Upgradable to dual processing	Upgradable to dual processing
Cache	512-KB second level ECC cache	512-KB second level ECC cache
Processor Slots	2	2
Expansion Slots		
I/O (Total)	6	6
PCI	2	2
Shared PCI/EISA	4	4
RAM		
Standard	64 MB	64 MB
Maximum	512 MB using buffered EDO ECC DIMMs	512 MB using buffered EDO ECC DIMMs

Network Interface Controllers

Netelligent 10/100 TX PCI UTP (embedded)	Standard	Standard
Netelligent Dual 10/100 TX PCI UTP	Optional	Optional
Netelligent 100 FDDI PCI SAS Fiber-SC	Optional	Optional
Netelligent 100 FDDI PCI SAS Fiber-MIC	Optional	Optional
Netelligent 100 FDDI PCI DAS Fiber-SC	Optional	Optional
Netelligent 100 FDDI PCI SAS UTP	Optional	Optional
Netelligent 100 FDDI PCI DAS UTP	Optional	Optional
Netelligent 100 FDDI EISA SAS Fiber-MIC	Optional	Optional
Netelligent 100 FDDI EISA DAS Fiber-MIC	Optional	Optional
Netelligent 100 FDDI EISA SAS UTP	Optional	Optional
Netelligent 100 FDDI EISA DAS UTP	Optional	Optional
Netelligent 10T/2 PCI UTP/Coax	Optional	Optional
Netelligent 10 T PCI UTP	Optional	Optional
Netelligent 4/16 TR PCI IBM UTP/STP	Optional	Optional
Netelligent 16/4 TR PCI UTP/STP	Optional	Optional
NetFlex-3/P		
100 Base-TX UTP Upgrade Module	Optional (for NetFlex-3)	Optional (for NetFlex-3)
100Base-FX UTP Upgrade Module	Optional (for NetFlex-3)	Optional (for NetFlex-3)
100VG-AnyLAN UTP Upgrade Module	Optional (for NetFlex-3)	Optional (for NetFlex-3)
AUI to BNC Transceiver	Optional	Optional

Server Management

Compaq Insight Manager	Standard	Standard
Integrated Remote Console	Standard (requires additional modem)	Standard (requires additional modem)
Integrated Management Display	Optional	Optional
Automatic Server Recovery	Standard	Standard

	Compaq ProLiant 1600 6/266	Compaq ProLiant 1600 6/300
Server Management <i>(cont'd)</i>		
Server Health Logs	Standard	Standard
Recovery Server Option	Optional	Optional
Compaq Remote Insight Board	Optional	Optional
Storage		
Diskette Drives	1.44-MB	1.44-MB
CD-ROM Drives		
Standard	16X Max ¹ CD-ROM IDE	16X Max ¹ CD-ROM IDE
Optional	IDE or SCSI	IDE or SCSI
Hard Drives ²		
Standard	None	None
Optional	2.1-GB, 4.3-GB, 9.1-GB, 18.2-GB Pluggable Wide-Ultra SCSI-3 Drives 4.3-GB, 9.1-GB Pluggable Wide-Ultra SCSI-3 10,000 rpm Hard Drives	2.1-GB, 4.3-GB, 9.1-GB, 18.2-GB Pluggable Wide-Ultra SCSI-3 Drives 4.3-GB, 9.1-GB Pluggable Wide-Ultra SCSI-3 10,000 rpm Hard Drives
External Storage		
ProLiant Storage System Models/F1 and /F2	Optional	Optional
ProLiant Storage System Models/U1 and /U2		
SCSI Storage Expander	Optional	Optional
CD-Storage System		
Tower Model	Optional	Optional
Maximum Storage Capacity		
Internal	54.6 GB (3 x 18.2-GB hot plug drives), 81.9 GB Maximum ³	54.6 GB (3 x 18.2-GB hot plug drives), 81.9 GB Maximum ³
External	1.15 TB = (7 x 18.2-GB) x 9	1.15 TB = (7 x 18.2-GB) x 9
Tape Drives		
Optional	2/4-GB DAT, 4/8-GB DAT, 4/8-GB SLR, 12/24-GB DAT, TurboDAT AutoLoaders, 15/30-GB DLT, DLT 15 Cartridge Library Model 1530-1, DLT 15 Cartridge Library Models 3570-1 and 3570-2	2/4-GB DAT, 4/8-GB DAT, 4/8-GB SLR, 12/24-GB DAT, TurboDAT AutoLoaders, 15/30-GB DLT, DLT 15 Cartridge Library Model 1530-1, DLT 15 Cartridge Library Models 3570-1 and 3570-2
Controllers		
Standard	Integrated Dual Channel Wide-Ultra SCSI-3	Integrated Dual Channel Wide-Ultra SCSI-3
Optional	Wide-Ultra SCSI-3, Dual Channel Wide-Ultra SCSI-3, SMART-2SL Array, SMART-2DH Array	Wide-Ultra SCSI-3, Dual Channel Wide-Ultra SCSI-3, SMART-2SL Array, SMART-2DH Array
Interfaces		
Parallel	1	1
Serial	2	2
Pointing Device (mouse)	1	1
Graphics	1	1
Keyboard	1	1
External Wide-Ultra SCSI-3	1	1

FEATURES *(cont'd)*

Compaq ProLiant 1600

Compaq ProLiant 1600 6/266	Compaq ProLiant 1600 6/300
----------------------------	----------------------------

Interfaces *(cont'd)*

Network

RJ-45	1	1
AUI	1	1
BNC	Optional with an AUI to BNC converter	Optional with an AUI to BNC converter

Graphics

Integrated 1024 x 768 by 256 color noninterlaced 1-MB Video System

Standard	Standard
----------	----------

Monitors

V55 Color	Optional	Optional
V75 Color	Optional	Optional
V90 Color	Optional	Optional
P50 Color	Optional	Optional
P75 Color	Optional	Optional
P110 Color	Optional	Optional
P1610 Color	Optional	Optional
TFT450 Flat Panel Color	Optional	Optional
TFT500 Flat Panel Color	Optional	Optional
Integrated Management Display	Optional	Optional

Redundant Power Supply

Compaq Hot-Pluggable Redundant Power Supply

Optional	Optional
----------	----------

Keyboard

Keyboard and Mouse	Standard	Standard
--------------------	----------	----------

Supported System Software from Compaq

Compaq SmartStart	Standard	Standard
Compaq Insight Manager	Standard	Standard
Bayan VINES 6.x and 7.x	Optional	Optional
Microsoft Windows NT 3.51 and 4.x	Optional	Optional
Novell intraNetWare	Optional	Optional
Novell intraNetWare for Small Business	Optional	Optional
Novell intraNetWare SFT-III	Optional	Optional
Novell NetWare 3.20	Optional	Optional
Novell NetWare 4.10	Optional	Optional
IBM OS/2 2.x	Optional	Optional
IBM OS/2 Warp Family of Products	Optional	Optional
SCO OpenServer 5	Optional	Optional
SCO UnixWare 2.1.x	Optional	Optional
Solaris X86 2.5.x and 2.6	Optional	Optional

¹ Data transfer rate will vary from 150 KB/s to 2400 KB/s

² Hard drive specifications may vary slightly depending on vendor.

³ For Maximum storage, remove the CD-ROM for an additional 27.3-GB (3 x 9.1-GB drives)